

# QUO200 SURFACE

QUS200.C.D.F.24.840.DALI.WH



## SPECIFICATION TEXT

QUO200, RECESSED DOWNLIGHT, 60 DEG DIRECT LIGHT DISTRIBUTION, FACETED REFLECTOR & LENS OPTIC COMBINATION, UGR <19, LED SOURCE, 4000(K) CCT, DALI LED DRIVER, DIE CAST ALUMINIUM HOUSING & FITTING TRIM, FINISHED WHITE ( RAL9016 ). IP54 RATING. DIMENSIONS: (ØxH) 228 X 100MM


## PRODUCT IMAGE




## TECHNICAL DETAILS

- Light Distribution: Direct, 60° Beam Angle
- Optic: Faceted reflector & Lens Optic
- Connected Load: 24W / DC 580mA
- Light Source: LED
- Integral Driver: DALI
- Nett luminous flux of luminaire: 3150lm
- Luminaire efficacy: >131lm/W
- Colour Temperature: 4000K
- MacAdams Ellipse: ≤4 SDCM
- Colour Rendering Index min.: >80 Ra
- Ingress Protection: IP54 below ceiling
- IK Rating: IK08
- Lumen Depreciation: L70 B50 @ 70,000Hrs
- Operating Hours: >50,000Hrs

## DIMENSIONAL DETAIL



## PHOTOMETRIC CURVE



230 V  
50 Hz

